

.223 Rem. SWISS P Ball

4.1 g/ 63 gr


Most accurate TFMJ round

Enhanced penetration due to tombac plated steel jacketed bullet

Preserves the weapon's service life

Coordinated ballistics with SWISS P Target, Styx Action and Armour Piercing rounds

Optional with heavy metal free ignition



Cartridge	5.56×45/ .223 Rem.	
Projectile	TFMJ, 4.1 g/63 gr	
Projectile material	tombac plated steel jacket, totally encapsulated lead core	
Ballistic coefficient G1	0.3678 (ICAO)	
Primer/optional	SINOXID/SINTOX® – non toxic	
Case material	CuZn – alloy	
Cartridge weight	12.2 g	
Performance		
Term of reference	C.I.P.	
Mean chamber pressure	max. 4300 bar	(21 °C)
Mean muzzle velocity	930 ± 15 m/s (3051 ± 49 fps)	600 mm barrel
Mean muzzle energy (Min–Max)	1773 J (1716–1831 J)	
Accuracy at 300 m	$s_a \leq 50$ mm	500 mm barrel
Packaging		
Standard cardboard box	10rds/clip, 50rds/cardboard box, 200rds/SLD-PVC, 1000rds/cardboard box, 50000rds EU pallet	

Images, drawings, technical details and in particular head stamps are for illustration purpose only, which do not necessarily correspond to actual products. All information and specifications shown in factsheets are non-binding and subject to alterations without prior notice at any time. 01.2023

SwissP Defence AG | info@swiss-p.com | www.swiss-p.com

SWISS 
The Sniper's Choice